Instant Road Repair RED 6mm Cold Lay Asphalt Concrete





6mm grade - For permanent repairs to cushions and ramps, bus lanes, cycle tracks, bus stops and colour coded car parking.

- Easy work formula
- Easier to compact
- HAPAS Approved since 2002
- Instantly trafficable
- No waste, resealable buckets
- Depth: 15-100mm

Applications

Instant Road Repair 6mm red is a HAPAS Approved Permanent Cold Lay Surfacing Asphalt Concrete for first time permanent repairs to cushions and ramps, bus lanes, cycle tracks, bus stops and colour coded car parking. It offers the benefits of an instant, first time permanent reinstatement, which when compacted, can be trafficked immediately.

Technical

UltraCrete Instant Road Repair 6mm red includes fully graded, high PSV interlocking aggregate as well as specially formulated bitumen, containing polymers and flexibilisers. It also forms part of the UltraCrete HAPAS Approved Ironwork Reinstatement System. It is satisfactory for use as a PCSM in accordance with Appendix A2.4 of the New Roads and Street Works Act 1999: Specification for the Reinstatement of Openings in Highways (SROH), Third Edition, April 2010.

Application for a Pothole Repair

- 1. Ensure area is clean from debris
- 2. Seal the pothole edges ad substrate using UltraCrete SCJ
- 3. Fill in hole with Instant Road Repair 6mm red
- 4. Tamp down

Application for First Time Permanent Repair

1. Saw cut a 'picture frame' around the repair or reinstatement area.

- 2. Ensure the area is clear of debris.
- 3. Seal vertical edges and substrate with SCJ.
- Reinstatements requiring up to 60mm in depth can be achieved by using the layer-on-layer method.

- Easy to apply
- For planned and reactive repairs
- Use in all weathers
 - 4. Apply the product to a depth of approximately 45mm and compact
 - to 30mm in order to achieve your first layer.
 - 5. Re-apply SCJ Edge Sealant to vertical edges before a second layer
 - of Instant Road Repair is applied.
 - 6. Repeat step 4 to achieve the 60mm depth.

Note: All compaction should be carried out in accordance with Appendix 8 of the SROH* 2010.

If overbanding is required, apply UltraCrete Instaband ECO.

Storage

Store in a cool and well-ventilated place.

Shelf life

Shelf life in correct conditions for sealed goods is 6 months.

Handling guidelines

UltraCrete Instant Road Repair is manufactured and delivered within as short a time as possible to ensure fresh easy to lay material is supplied. It should be noted that bags on pallets, particularly those at the bottom, could appear firm. Applying light pressure to the edge of the bag will restore the material to its normal consistency.

Health, Safety and Environmental

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste





compliance number: 396



responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from instarmac.co.uk

Quality assurance

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001. Our products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.

| PSV | 65 |
|----------------|---|
| Colour | red |
| Also available | black 6mm black 10mm |
| Coverage | Approx 1m ² at 12-15mm compacted, depending on the surface regularity of the reinstatements |
| Unit/packaging | 25kg bucket (52 units per pallet) |

Technical data

Contact Us

Instarmac^{*} Group plc, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom Tel: +44 (0) 1827 254400

Email: email@instarmac.co.uk Order: orders@instarmac.co.uk Website: instarmac.co.uk

Vers 3.02.23 Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at www.ultracrete.co.uk

